



## Arius Platinum Aluminum Plates

Plate size	Riedell boot size	Plate length in mm	Wheelbase in mm	Toe length* in mm	Heel length** in mm	Plate length in inches	Wheelbase in inches	Plate weight each / pair in ounces	Plate assembly weight*** each / pair in ounces
3	3, 3 1/2	223	134	59	30	8 3/4	5 1/4	5.96 / 11.92	12.02 / 24.04
4	4, 4 1/2	233	144	59	30	9 3/20	5 2/3	6.06 / 12.12	12.12 / 24.24
5	5, 5 1/2	239	150	59	30	9 2/5	5 9/10	6.16 / 12.32	12.22 / 24.44
6	6, 6 1/2	245	156	59	30	9 2/3	6 1/8	6.26 / 12.52	12.32 / 24.64
7	7, 7 1/2	251	162	59	30	9 9/10	6 3/8	6.36 / 12.72	12.42 / 24.84
8	8, 8 1/2	257	168	59	30	10 1/10	6 5/8	6.46 / 12.92	12.52 / 25.04
9	9, 9 1/2	263	174	59	30	10 7/20	6 17/20	6.56 / 13.12	12.62 / 25.24
10	10, 10 1/2	269	180	59	30	10 3/5	7 1/10	6.66 / 13.32	12.72 / 25.44
11	11, 11 1/2	275	186	59	30	10 4/5	7 1/3	6.76 / 13.52	12.82 / 25.64
12	12, 12 1/2, 13	281	192	59	30	11 1/20	7 9/16	6.86 / 13.72	12.92 / 25.84

\*Toe length is distance from center of front axle to front end of plate

\*\*Heel length is distance from center of back axle to back end of plate

\*\*\*Plate assembly includes Axis Pins, trucks, Split Butterfly Cushions, lock nuts

This chart is a guide - recommendations from the manufacturer. Plate size and mounting can vary for skaters. Skates mounted at Riedell will use this guide unless otherwise specified.